

# Robust Configuration Management

<draft-cole-netconf-robust-config-00.txt>

Robert G. Cole<sup>1</sup>    Dan Romascanu<sup>2</sup>

<sup>1</sup>Johns Hopkins University  
robert.cole@jhuapl.edu

<sup>2</sup>Avaya  
dromasca@avaya.com

24 March 2009 / IETF-San Francisco

## Objectives and Benefits

Objective is to develop a Verify and Validate capability tied to <commit> and <edit-config> NETCONF operations.

- Verification - checking against a set of rules.
- Validation - measuring behavior against expectations.

Benefits include:

- Minimize faulty configuration,
- Minimize disconnects in networks with no 'out-of-band' access, e.g., MANETs or DTNs.
- Provide opportunity for device modelers to associate/recommend tests tied to specific configuration items.

## Background - NETCONF and YANG Capabilities

- NETCONF :confirmed-commit capability allows the agent (not server) to run a set of Validation tests prior to issuing a 'confirming commit' to the server.
- NETCONF <edit-config> operation allows for for some Verification (and maybe Validation) checking.
- The YANG 'must' statement extends the :validate capability for improved Verification checking through constraint definitions.

## Background - Related OAM Capabilities

- RMON provides for general specification of active network tests, see 'protocolID', AppLocalIndex (APM-MIB) [3], SSPM-MIB [4], TPM-MIB [5].
- Operations and Management (OAM) capabilities for Carrier Class Ethernet [6-9] and MPLS-based services [10-13] will provide for automatic Validation testing.
  - I.e., continuity, fault, isolation and performance tests and SLA monitoring [6-9].

## Proposal - Enhance V&V

Enhance/develop the NETCONF Verification and Validation capability for <commit> and <edit-config> operations:

- Specify a set of tests associated with proposed configuration.
- Move Validation testing from the agent to the server, i.e., the remote managed device.
- Define capability to specify pass/fail criteria.
- One specific class of tests would be network tests (network test imply a set of active measurement probes injected into the network).
- Better flesh out relationship of Verification versus Validation within the context of configuration management and explore protocol implications.

## Proposal - Enhance V&V

Potential test specification options:

- Local or remote script specifications, i.e., <commit> passes an URL pointing to the script and passes a specification of 'success'
- Tests separately specified via a modeling language, similar to SSPM-MIB (for network test specification) but using YANG, and passed with the <commit> operation.
- Tests are associated with specific configuration objects within the device's (YANG) model.
  - Success criteria, but not specific value, defined in module.

## Questions

- How to specify specific tests and their benefits?
- Should specific tests be tied to specific configuration parameters within the device's data model?
- Do we limit Validation testing to the <commit> and limit Verification testing to the <copy-config> or allow Validation testing to <copy-config> through the 'writable-running' capability?
- Is there interest in pursuing this objective?
- If yes, then next steps might be:
  - Continue to flesh out this draft and protocol implications,
  - Investigate YANG model to define (or point to) active tests or
  - Investigate YANG model which embeds active tests within a YANG device model,
  - Investigate means to specify pass/fail criteria.
  - Investigate security implications and solutions.

## References

- 1 Enns, R., Editor, *NETCONF Configuration Protocol*, IETF RFC 4741, December 2006. <http://www.rfc-editor.org/rfc/rfc4741.txt>
- 2 Bjorklund, M., Editor, *YANG - A data modeling language for NETCONF*, IETF Draft, <draft-ietf-netmod-yang-01.txt>, 29 August 2008.  
<http://www.ietf.org/internet-drafts/draft-ietf-netmod-yang-04.txt>
- 3 Waldbusser, S., *Application Performance Monitoring MIB*, Internet Engineering Task Force (IETF), RFC 3729, March (2004). <http://www.rfc-editor.org/rfc/rfc3729.txt>
- 4 Kalbfleisch, C., Cole, R.G. and D. Romascanu, *Definition of Managed Objects for Synthetic Sources for Performance Monitoring Algorithms*, IETF RFC 4149, August 2005.  
<http://www.rfc-editor.org/rfc/rfc4149.txt>
- 5 Dietz, R. and R.G. Cole, *A MIB for Transport Performance Monitoring*, Internet Engineering Task Force (IETF), RFC 4150, July (2005). <http://www.rfc-editor.org/rfc/rfc4150.txt>



## References (cont.)

- ⑥ IEEE 802.1, *IEEE 802.1ag - Connectivity Fault Management*, September (2007).
- ⑦ IEEE 802.3, *IEEE 802.3ah - Ethernet in the First Mile*, December (2005).
- ⑧ ITU-T Study Group 13, *ITU-T Y.1730 - Requirements for OAM Functions in Ethernet-based Networks and Ethernet Services*, January (2004)
- ⑨ ITU-T Study Group 13, *ITU-T ffY.1731 - OAM Functions and Mechanisms for Ethernet-based Networks*, May (2006).
- ⑩ Nadeau, T., Morrow, M., Swallow, G., Allan, D., and S. Matsushima, *Operations and Management (OAM) Requirements for Multi-Protocol Label Switched (MPLS) Networks*, RFC 4377, February 2006. <http://www.rfc-editor.org/rfc/rfc4377.txt>

## References (cont.)

- 11 Allan, D. and T. Nadeau, *A Framework for Multi-Protocol Label Switching (MPLS) Operations and Management (OAM)*, RFC 4378, February 2006. <http://www.rfc-editor.org/rfc/rfc4378.txt>
- 12 Yasukawa, S., Farrel, A., King, D. and T. Nadeau, *Operations and Management (OAM) Requirements for Point-to-Multipoint for Multi-Protocol Label Switched (MPLS) Networks*, RFC 4687, September 2006. <http://www.rfc-editor.org/rfc/rfc4687.txt>
- 13 Vigoureux, M., *Requirements for Operations and Management (OAM) in MPLS Transport Network*, Internet Engineering Task Force (IETF) <draft-ietf-mpls-tp-aom-requirements-01.txt>, March (2009). <http://www.ietf.org/internet-drafts/draft-ietf-mpls-tp-aom-requirements-01.txt>
- 14 ITU-T Study Group 13, *ITU-T Y.1710 - Requirements for OAM Functionality in MPLS Networks*, (2002).