

Resource ReserVation Protocol- Traffic Engineering (RSVP-TE) Path Diversity using Exclude Route

[draft-ietf-teas-lsp-diversity-01](#)

IETF 92 – TEAS WG

Editors:

Zafar Ali

zali@cisco.com

George Swallow

swallow@cisco.com

Fatai Zhang

ZhangFatai@huawei.com

Dieter Beller

Dieter.Beller@alcatel-lucent.com

+ 17 contributors

see next slide

Contributors

- Igor Bryskin, ADVA Optical Networking
- Daniele Ceccarelli, Ericsson
- Oscar Gonzalez de Dios, Telefonica I+D
- Dhruv Dhody, Huawei Technologies
- Don Fedyk, Hewlett-Packard
- Clarence Filsfils, Cisco Systems
- Xihua Fu, ZTE
- Gabriele M. Galimberti, Cisco Systems
- Ori Gerstel, SDN Solutions Ltd.
- Matt Hartley, Cisco Systems
- Kenji Kumaki, KDDI Corporation
- Ruediger Kunze, Deutsche Telekom AG
- Lieven Levrau, Alcatel-Lucent
- Cyril Margaria, Juniper
- Julien Meuri, France Telecom Orange
- Yuji Tochio, Fujitsu
- Xian Zhang, Huawei Technologies

Agenda

- Changes w.r.t. the previous version
- Next steps

Changes

- Lou's review comments from IETF 91 addressed:
 - Explanatory text added re RSVP FEC in Client-Initiated Identifier section (section 1.1) referencing [RFC3209](#)
 - Added note on border/ transit node processing. Specifically, only nodes in the domain that perform path computation are expected to understand the Diversity subobject; other transit nodes are not required to process it.
 - DI type values defined in this draft
 - IANA section cleaned up (all suggested values removed)

Next Steps

- Solicit feedback/comments from the group.
- No open issues.
- Editors are of the opinion that the I-D is ready now for WG last call.

Thank You!