

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: May 1, 2020

D. Shytyi  
L. Beylier  
SFR  
L. Iannone  
Telecom ParisTech  
October 29, 2019

A YANG Module for uCPE management.  
draft-shytyi-opsawg-vysm-05

## Abstract

This document provides a YANG data model for uCPE management (VYSM) and definition of the uCPE equipment. The YANG Service Model serves as a base framework for managing an universal Customer-Premises Equipment (uCPE) subsystem. The model can be used by a Network Service Orchestrator.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 1, 2020.

## Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	2
2. Terminology . . . . .	2
3. Universal CPE . . . . .	3
3.1. uCPE purpose . . . . .	4
3.2. uCPE VNF ecosystem example . . . . .	4
3.3. Internal uCPE service example . . . . .	5
4. YANG Service Model for uCPE management . . . . .	5
5. uCPE YANG Service Model tree diagram overview . . . . .	7
6. Specification of the VNF YANG Service Model . . . . .	8
7. XML example . . . . .	13
8. Security Considerations . . . . .	16
9. IANA Considerations . . . . .	16
10. Acknowledgements . . . . .	16
11. Normative References . . . . .	17
Authors' Addresses . . . . .	17

## 1. Introduction

Network Function Virtualization is a technology that allows to virtualize the network services running on dedicated hardware. This technology became a base for universal Customer-Premises Equipment (uCPE). This document defines the uCPE as hardware with x86 capabilities that has a hypervisor. In other words, uCPE is a host that may run multiple Virtual Machines with guest OSs, where each Guest OS may represent a Physical Network Function. This document presents the YANG Service Model (VYSM) to manage from an Orchestrator the infrastructure inside the uCPE.

## 2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

Link - is an entity that enables link layer communication of nodes.

Port - node connector to the link.

NE - Network Element.

NSYM - Network Service Yang Module.

VYSM - VNF YANG Service Model.

### 3. Universal CPE

Firstly, this document defines the platform that is controlled with VYSM - universal CPE (uCPE). The uCPE as hardware with x86 capabilities that is generally running Linux distribution with additional virtualisation layer. Virtualization layer provides virtual compute, virtual storage and virtual network resources. Each VNF running in the uCPE requires the amount of virtual resources (for example: 4 vCPUs, 4GB RAM, 40GB storage, 4 vPorts). VNFs MAY be interconnected between each other and physical ports via Virtual Networks. Topology construction and VM lifecycle management is allowed via high level interface (Configuration can be done in the same transaction). The figure below presents the uCPE architecture.

VNF1	VNF2	VNF3	
Virtual Compute	Virtual Storage	Virtual Networks	uCPE software
PHY x86 processor	RAM+PHY storage	PHYSical ports	uCPE Hardware

The next elements can be managed in the uCPE:

- o Virtual Network Functions:
  - \* Number of assigned vCPUs.
  - \* Size of allocated RAM.
  - \* VNF day0 config (bootstrap).
  - \* vLinks that are attached to the VNF.
- o Virtual Switches:
  - \* vLinks that are attached to the vSW.
- o Virtual Links(vLinks).
- o Physical Ports of the uCPE.



- o virtual WAN Optimistaion
- o vWireless LAN controller
- o Other...

### 3.3. Internal uCPE service example

The VNF in the uCPE could be a vRouter or vFirewall or an SD-WAN that is not a default part of virtual network resources of the uCPE. Multiple VNFs MAY be instantiated in the uCPE. With support of links and swithes, VNFs MAY participate a service chains. Example of service chains (Note that virtual switch "vs(WAN)" connected to LAN ports and vSW(WAN) is connected to WAN ports):

- o vSW(WAN)-l1-vRouter(vCPE)-l2-vSW(LAN).
- o vSW(WAN)-l1-vRouter(vCPE)-l2-vSW(Service)-l3-vFirewall-14-vSW(LAN).
- o vSW(WAN)-l1-vRouter(vCPE)-l2-vSW(Service1)-l3-vFirewall-14-vSW(Service2)-15-SD-WAN-16-vSW(LAN).
- o vSW(WAN)-l1-SDWAN-l2-vSW(Service)-l3-vFirewall-14-vSW(LAN).
- o

```

vSW(WAN1)--vRouter---+
                        +--vLoadBalance  vFirewall--vSW(LAN)
vSW(WAN2)--vRouter---+   |
                        +--vSW(Service1)+   |

```

o

```

vSW(WAN1)--vRouter(ISP1)---+
                        +--SD-WAN          vFirewall--vSW(LAN)
vSW(WAN2)--vRouter(ISP2)---+   |
                        +--vSW(Service1)+   |

```

## 4. YANG Service Model for uCPE management

Secondly, this document defines and classifies the VYSM as Network Service YANG Module(NSYM) layer component RFC 8199 [RFC8199]. Thus it inherits the characteristics of the NSYM Layer. VYSM is a modeled

representation of the specific service requirements. It provides abstraction of services configuration and operations that MAY be implemented in Network Elements (NEs). Thus VYSM does not describe all configuration to be performed on the devices, but provides the configuration that is required for the "Network Service to Network Element(s)" decomposition process RFC 8199 [RFC8199]. Example of the decomposition is presented in the figure below.

The Network Service YANG module exposes the configuration commands via the Northbound interfaces of the orchestrator. Therefore the set of the commands modeled in the VYSM can be inputted via Northbound interfaces (for example CLI). In the example the command "vm VNF1" is passed via Northbound interface to the orchestrator. It defines the virtual machine name. Further the same configuration MAY be transformed to the one or multiple Network Element payloads (for example xml for NETCONF) that carry an equivalent of commands such as "nf nf-name VNF1"

```

+-----+
|               |
|   config t   |
|     vm VNF1  |
|               |
+-----+
#
#
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
:
: | Network Service YANG Module |
: +-----+-----+-----+-----+-----+-----+-----+-----+
: #
: ##### orchestrator
: # # #
: '-----' '-----' '-----'
: 'Module1' ' Module 2' ' Module3' <= Network Element
: '-----' '-----' '-----' YANG Modules
: # # #
: # # #####
: #### ##### #
: # # #
+-----+-----+-----+-----+-----+-----+-----+-----+
# # #
Network # element 1 Network # element 2 Network # element3
+-----+-----+-----+-----+-----+-----+-----+-----+
| domains domain VNF1| |tenants tenant name VNF1| |nf nf-name VNF1|
+-----+-----+-----+-----+-----+-----+-----+-----+

```

5. uCPE YANG Service Model tree diagram overview

This section provides an overview of the Service YANG Model (VSYM) that MAY be made with "pyang" utility. The figure below presents the tree diagram of VYSM.

```

module: ietf-ucpe
  +--rw ucpe* [name]
    +--rw name          string
    +--rw links* [link]
      | +--rw link      string
    +--rw phyInterfaces* [interface]
      | +--rw interface  string
      | +--rw ports* [port]
      |   +--rw port      string
      |   +--rw link?    -> ../../../../links/link
    +--rw switches* [switch]
      | +--rw switch     string
      | +--rw ports* [port]
      |   +--rw port      string
      |   +--rw name?     string
      |   +--rw link?    -> ../../../../links/link
    +--rw vms* [vm]
      +--rw vm           string
      +--rw ports* [port]
        | +--rw port      string
        | +--rw name?     string
        | +--rw link?    -> ../../../../links/link
      +--rw ram?         uint64
      +--rw cpu?         uint64
      +--rw storages* [id]
        | +--rw id         string
        | +--rw location?  string
      +--rw day0-config
        +--rw location?    string
        +--rw day0-var-path? string
        +--rw variable* [name]
          +--rw name      string
          +--rw value?    string

```

## 6. Specification of the VNF YANG Service Model

This section presents the specification of the VYSM.

```

<CODE BEGINS> file "ietf-ucpe@2019-10-28.yang"
module ietf-ucpe {
  namespace "urn:ietf:params:xml:ns:yang:ietf-ucpe";
  prefix ietf-ucpe;

  organization
    "SFR";
  contact

```



```
"Dmytro Shytyi
  EMail:ietf.dmytro@shytyi.net";
description
  "This is a Network Function Virtualization (NFV) YANG
  service model.

  Copyright (c) 2019 IETF Trust and the persons identified as
  authors of the code.  All rights reserved.

  Redistribution and use in source and binary forms, with or
  without modification, is permitted pursuant to, and subject to
  the license terms contained in, the Simplified BSD License set
  forth in Section 4.c of the IETF Trust's Legal Provisions
  Relating to IETF Documents
  (https://trustee.ietf.org/license-info).

  This version of this YANG module is part of RFC XXXX
  (https://www.rfc-editor.org/info/rfcXXXX); see the RFC itself
  for full legal notices.";

revision 2019-10-28 {
  description
    "Yang model with vPorts assigned to the interfaces";
  reference
    "draft-shytyi-opsawg-vysm-05";
}
revision 2019-10-19 {
  description
    "Yang model was cleaned. Interfaces added";
  reference
    "draft-shytyi-opsawg-vysm-04";
}
revision 2019-09-16 {
  description
    "Added Oday config for VNFs.
    Yang model modified according
    to the received comments.";
  reference
    "draft-shytyi-opsawg-vysm-00";
}
revision 2018-01-07 {
  description
    "Initial revision.";
  reference
    "draft-shytyi-netmod-vysm-01";
}

list ucpe {
```

```
key "name";
leaf name {
  type string;
  description
    "ID of uCPE where
     a service is instantiated";
}
list links {
  key "link";
  leaf link {
    type string;
    description
      "Name of the virtual link from the pool
       of the links";
  }
  description
    "Pool of the virtual links that connect VMs and
     Interfaces";
}
list phyInterfaces {
  key "interface";
  leaf interface {
    type string;
    description
      "Name of physical interface";
  }
  list ports {
    key "port";
    leaf port {
      type string;
      description
        "Name of the connector";
    }
    leaf link {
      type leafref {
        path "../..../links/link";
      }
      description
        "Link that is connected to
         the port via connector";
    }
    description
      "Set of the connectors the
       physical interface has";
  }
  description
    "Set of physical interfaces";
}
```

```
list switches {
  key "switch";
  leaf switch {
    type string;
    description
      "Name of the forwarding domain";
  }
  list ports {
    key "port";
    leaf port {
      type string;
      description
        "Name of the connector";
    }
    leaf name {
      type string;
      description
        "Name of the
        subconnector";
    }
    leaf link {
      type leafref {
        path "../.../links/link";
      }
      description
        "Link that is connected to the
        switch via port";
    }
    description
      "Set of the connectors the
      forwarding domain has";
  }
  description
    "Set of the forwarding domains";
}
list vms {
  key "vm";
  leaf vm {
    type string;
    description
      "ID of the Virtual Machine";
  }
  list ports {
    key "port";
    leaf port {
      type string;
      description
        "Name of the connector";
    }
  }
}
```

```
    }
    leaf name {
      type string;
      description
        "Name of
         the subconnector";
    }
    leaf link {
      type leafref {
        path "../../../../../links/link";
      }
      description
        "Link that connects the
         VM with a switch or Interface
         via connector";
    }
  }
  description
    "Set of Virtual Machine connectors";
}
leaf ram {
  type uint64;
  description
    "Size of RAM to allocate for
     the Guest OS";
}
leaf cpu {
  type uint64;
  description
    "Number of vCPUs to
     allocate for the Guest OS";
}
list storages {
  key "id";
  leaf id {
    type string;
    description
      "Number of
       vDisk attached to the VM";
  }
  leaf location {
    type string;
    description
      "External location where
       the image (ex.qcow2) is saved.";
  }
}
description
  "Virtual storage/vDisk
   attached to the Virtual Machine";
```

```

    }
    container day0-config {
      leaf location {
        type string;
        description
          "0day configuration location";
      }
      leaf day0-var-path {
        type string;
        description
          "path of the file
          that contains the 0day variables";
      }
      list variable {
        key "name";
        leaf name {
          type string;
          description
            "variable name";
        }
        leaf value {
          type string;
          description
            "variable value";
        }
        description
          "list of variables";
      }
      description
        "0day configuration:init config";
    }
    description
      "Set of the Virtual Machines configured
      on the universal Customer-Premises Equipment";
  }
  description
    "This is an uCPE management service";
}
}


```

<CODE ENDS>

## 7. XML example

The XML example below presents the configuration of the next service in the uCPE, where: vSW(LAN), vSW(WAN), vSW(Service) - virtual switches; l1,l2,l3,l4 - virtual links; VMs represent PNFs (Physical

Network Functions) that could be bootstrapped with 0day config/license.



```

<ucpe xmlns="urn:ietf:params:xml:ns:yang:ietf-ucpe">
  <name>ucpe1</name>
  <links>
    <link>l1</link>
  </links>
  <links>
    <link>l2</link>
  </links>
  <links>
    <link>l3</link>
  </links>
  <links>
    <link>l4</link>
  </links>
  <switches>
    <switch>lan</switch>
    <ports>
      <port>10</port>
      <name>l2p10</name>
      <link>l2</link>
    </ports>
  </switches>
  <switches>
    <switch>service</switch>
    <ports>
      <port>10</port>
      <name>l3p10</name>
      <link>l3</link>
    </ports>
    <ports>
      <port>11</port>
      <name>l4p10</name>
      <link>l4</link>
    </ports>
  </switches>
</ucpe>

```

```
<switches>
  <switch>wan</switch>
  <ports>
    <port>10</port>
    <link>l1</link>
  </ports>
</switches>
<vms>
  <vm>VNF-vCPE</vm>
  <ports>
    <port>1</port>
    <name>l1p1</name>
    <link>l1</link>
  </ports>
  <ports>
    <port>2</port>
    <name>l4p2</name>
    <link>l4</link>
  </ports>
  <ram>2048</ram>
  <cpu>2</cpu>
  <storages>
    <id>1</id>
    <location>http://192.168.2.1/vCPE-x86.qcow2</location>
  </storages>
  <day0-config>
    <location>https://192.168.2.1/vCPE-day0.iso</location>
    <day0-var-path>/config.rom</day0-var-path>
    <variable>
      <name>hostname</name>
      <value>IETF-vCPE</value>
    </variable>
    <variable>
      <name>ipaddress</name>
      <value>192.168.1.2 255.255.255.0</value>
    </variable>
  </day0-config>
</vms>
<vms>
  <vm>VNF-vFirewall</vm>
  <ports>
    <port>1</port>
    <name>l3p1</name>
    <link>l3</link>
  </ports>
  <ports>
    <port>2</port>
    <name>l2p2</name>
```

```
    <link>l2</link>
  </ports>
  <ram>2048</ram>
  <cpu>2</cpu>
  <storages>
    <id>1</id>
    <location>http://192.168.2.1/vFirewall-x86.qcow2</location>
  </storages>
  <day0-config>
    <location>https://192.168.2.1/vFirewall-day0.iso</location>
    <day0-var-path>/config.rom</day0-var-path>
    <variable>
      <name>hostname</name>
      <value>vFirewall</value>
    </variable>
    <variable>
      <name>ipaddress</name>
      <value>192.168.1.3 255.255.255.0</value>
    </variable>
  </day0-config>
</vms>
</ucpe>
```

## 8. Security Considerations

At this time, no security considerations are addressed by this memo.

## 9. IANA Considerations

No request to IANA at this time.

## 10. Acknowledgements

The authors would like to thank:

- o Mahesh Jethanandani.
- o Robert Varga.
- o Bill Wu.
- o Joe Clarke.
- o Tom Petch.
- o Martin Bjorklund.



o SchAP.nwA[currency units]lder JA1/4rgen.

for their valuable comments.

## 11. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC8199] Bogdanovic, D., Claise, B., and C. Moberg, "YANG Module Classification", RFC 8199, DOI 10.17487/RFC8199, July 2017, <<https://www.rfc-editor.org/info/rfc8199>>.

## Authors' Addresses

Dmytro Shytyi  
SFR  
Paris , Ile-de-France  
France

Email: [ietf.dmytro@shytyi.net](mailto:ietf.dmytro@shytyi.net)  
URI: <https://dmytro.shytyi.net>

Laurent Beylier  
SFR  
Paris , Ile-de-France  
France

Email: [laurent.beylier@sfr.com](mailto:laurent.beylier@sfr.com)

Luigi Iannone  
Telecom ParisTech  
Paris , Ile-de-France  
France

Email: [luigi.iannone@telecom-paristech.fr](mailto:luigi.iannone@telecom-paristech.fr)