

A YANG Data Model for Client Signal Performance Monitoring

IETF 108 CCAMP

draft-zheng-ccamp-client-pm-yang-02

Authors:


Haomian Zheng (zhenghaomian@huawei.com)

Italo Busi (Italo.Busi@huawei.com)

Yanlei Zheng (zhengyanlei@chinaunicom.cn)

Model Relationship

- Performance need to be monitored for operation need for the client signal in [draft-ietf-ccamp-client-signal-yang-01](#);
- Potential Parameters to be monitored:
 - Latency, BER, Packet Loss, Bandwidth, Jitter, Byte/Packet Number, Power, etc...



Changes since -01 (in pm module)

- Combined two PM models (Ethernet, transparent) into one;
- Added the measure-method to specify how to do PM;
 - Measure by loopback or measure at ingress;

```
module: ietf-service-pm
  +-rw performance-monitoring
    +-rw service-pm* [service-name]
      +-rw service-name
      +-rw task-pm-enable?
      +-rw granularity?
      +-rw performance-data-config* [parameter-name]
        |   +-rw parameter-name    identityref
        |   +-rw measure-method?   identityref
```


To index the service;

Specify PM method;

union
boolean
identityref
identityref
identityref

Changes since -01 (in pm module)

- Re-formatted the service-pm structure;



OAM Augmentation in PM Model

```
augment /svc-pm:performance-monitoring/svc-pm:service-pm:  
  +--rw oam-config  
    +--rw source  
      +--rw md-name?          string  
      +--rw ma-name?          string  
      +--rw ma-level?         string  
      +--rw meg-id?           string  
      +--rw meg-level?        string  
      +--rw mep-id?           uint8  
      +--rw remote-mep-id?    uint8  
    IEEE 802.1Q  
  
    +--rw destination  
      +--rw md-name?          string  
      +--rw ma-name?          string  
      +--rw ma-level?         string  
      +--rw meg-id?           string  
      +--rw meg-level?        string  
      +--rw mep-id?           uint8  
      +--rw remote-mep-id?    uint8  
    IEEE 802.1Q  
    Y.1731  
  
    +--rw cc-interval?       identityref  
    +--rw lm-interval?       identityref  
    +--rw dm-interval?       identityref
```

This Augmentation applies to Ethernet Only.

We want to hear from WG...

- Is the problem valid?
- Match with the WG scope?
- Request for WG Adoption.

Github: <https://github.com/haomianzheng/IETF-ACTN-YANG-Model/tree/master/YANG/ccamp/client-pm>