

vCard 4.0

[draft-ietf-vcarddav-vcardrev-10]

Simon Perreault
Viagénie

simon.perreault@viagenie.ca

Pete Resnick
Qualcomm

presnick@qualcomm.com

Vcarddav Working Group Meeting
IETF-77, Anaheim

210-03-24

Major Changes

- UTF-8 is now the only possible character set, ever, in any circumstance.
 - If present, the “charset” parameter's value MUST be “UTF-8”.
- Created the CALSCALE parameter.
 - Used on date-valued properties.
 - If present, is “gregorian”, iana-token, or x-name.

The Bizarre and Wonderful “XML” Property

- The three following vCards are equivalent.

```
<?xml version="1.0"?>
<vcards xmlns="urn:ietf:params:xml:ns:vcard-4.0">
  <vcard>
    <fn><text>John Doe</text></fn>
    <email><text>jdoe@example.com</text></email>
  </vcard>
</vcards>
```

```
BEGIN:VCARD
VERSION:4.0
XML:<fn><text>John Doe>/text></fn>\n
  <email><text>jdoe@example.com</text></email>
END:VCARD
```

```
BEGIN:VCARD
VERSION:4.0
FN:John Doe
EMAIL:jdoe@example.com
END:VCARD
```

Next Steps

- WGLC

This is the last slide.