DHCPv6 class based prefix (draft-bhandari-dhc-class-based-prefix-01)

IETF 83, March 2012

Authors: Shwetha Bhandari (Cisco) Sri Gundavelli(Cisco) Gaurav Halwasia (Cisco) Sindhura Bandi (Cisco), Hui Deng (China Mobile)

Problem Statement

- DHCPv6 Server can delegate longer prefixes and IA_NA assignments from shorter prefix learnt via DHCPv6 PD (RFC 3633)
 - Further delegation of a delegated prefix- DHCPv6 PD client assuming the role of DHCPv6 Server needs to delegate prefix or assign IA_NA based on prefix property.
- DHCPv6 PD Client Can request for prefix with specific properties
- DHCPv6 IA_NA Client Can request for IA_NA from a prefix range with specific properties
- Applications can use prefix with specific properties/color

DHCPv6 Prefix delegation – DHCPv6 PD provides no semantics to request and associate prefix with specific properties today

Proposed Extension

• New DHCPv6 option to associate Prefix with its properties:

option-code: OPTION_PREFIX_CLASS (TBD) option-length: length of prefix-class prefix-class: Prefix class (binary string).

- DHCPv6 PD client To include OPTION_PREFIX_CLASS in DHCPv6 Solicit message
- DHCPv6 IA_NA client To include OPTION_PREFIX_CLASS in DHCPv6 Solicit message
- DHCPv6 Server to include OPTION_PREFIX_CLASS in:
 - OPTION_IAPREFIX option in Advertise messages for Prefix delegation
 - OPTION_IA_NA option in Advertise message for IA_NA assignment


Motivation/Use cases

- Mobile Network
 - Mobile gateway as a DHCPv6 PD client and a DHCPv6 Server serving DHCPV6 clients attached to it
 - Prefix coloring Prefix with different properties. Example:
 - Prefix is from local access network, non-mobile properties

 This prefix does not support mobility
 - Global home agent assigned, chained mobility This prefix is topologically anchored in the mobile node's home network. It has mobility properties.
 - Low latency suitable for Voice applications

Example: Mobile network

• Prefix color in mobile network: To support offload function for certain traffic in chained mobility scenario, the UE needs to use the right source address for the right application flows.



Changes since -00

Clean up of use-cases

Next Steps

- Authors appreciate feedback from the WG
- WG draft?