

draft-ietf-tsvwg-rsvp-pcn-03

Georgios Karagiannis, Anurag Bhargava



- Main Changes
- Received new comments
- Next steps



All comments worked out (including <u>PCN WG</u> ones) according to decisions taken on mailing list and IETF 84 meeting in Vancouver:

- changed status of draft from proposed standard to experimental
- modified description of Extended Virtual Destination Port, specifies that its length is different for IPv4 and IPv6 addresses

New comments raised by Lixia and Ken (1)

- Editorial comments:
 - Improve introduction section, organization and clarity of draft including a background section, better goal description and document structure description
 - Eliminate given terminology that is not used in the draft
 - Eliminate duplicated definitions of terminology
 - Refer to a section of a particular RFC (i.e., RFC 4860), instead of referring only to that particular RFC

New comments raised by Lixia and Ken (2)

- Elaborate rationale of why it is considered that the decision point is collocated with the PCN-ingress-node
 - Signaling solution focuses only on on-path signaling to support feedback loop from egress to ingress.
 - Off-path signaling support required between edges and centralized entity is out of scope
- Recommendation to re-visit SHOULDs
 - On further review, some SHOULDs to MUSTs
 - Other SHOULDs inherited from RFC 4860, RFC 6661, RFC 6662
 - Changes will be posted on the list



Next steps

- Update draft based on received comments
- Working Group Last Call after received comments are worked out?