

STOX: Core, Presence, Chat

Peter Saint-Andre
STOX WG
IETF 87, Berlin

Reviewers

- Thanks for the reviews!
 - Saúl Ibarra Corretgé
 - Mike De Vries
 - Robert Sparks

Core (I)

- Mapping of XMPP <service-unavailable/> to SIP 503 is broken
- In SIP, 503 means the remote server is unavailable, so using it for accounts (user@host) will break things badly
- Proposal (Robert Sparks): discourage mapping to 503 and explain why

Core (2)

- We don't have any text about DNS lookups for interdomain federation
- There is some old text in the -im document
- Proposal: move this text to -core, delete `_im` and `_pres` lookups, and modify it to cover federation in general

Core (3)

- No text right now about whether/how to populate the SIP “Reason-Phrase” or the `<text/>` element of XMPP `<error/>`
- Proposal (Mike De Vries): map SIP “Reason-Phrase” in Status-Line header to XMPP `<text/>` child of `<error/>` element

Presence

- Don't define handling of custom namespaces for detailed availability states
- Proposal (Mike De Vries): SIP-to-XMPP gateway to be responsible for including `<show/>` in the XMPP presence notification, and may also include the custom extension

Chat

- Add mapping between Chat State Notifications (XEP-0085) and the `isComposing` event (RFC 3994)?
- Add mapping between message receipts (XEP-0184) and MSRP REPORT chunks (RFC 4975)?