

Using BGP between PE and CE in EVPN

draft-li-l2vpn-evpn-pe-ce


Zhenbin Li, Junlin Zhuang
(Huawei Technologies)

IETF 88, Vancouver, BC, Canada

Introduction


- This draft is to introduce BGP between PE and CE in EVPN to complete the learning of local MAC addresses

Applications – Fast Convergence




- T1- When the MAC Advertisement Route from PE1 and the Ethernet A-D routes per ESI from PE1 and PE2 are received, PE3 can forward traffic destined to MAC A to both PE1 and PE2.
- T2- After T1, when the ESI connected to PE1 fails, PE1 MUST withdraw its Ethernet A-D route per ESI, then PE3 forwards traffic destined to MAC A to PE2 only.
- T3- After T2, PE1 MUST also withdraw the MAC advertisement routes (MAC A) that are impacted by the failure. Before PE2 learns MAC A and advertises a MAC route for MAC A, PE3 will treat traffic to MAC A as unknown unicast. If the behavior is to drop the unknown unicast based on administrative policy, the traffic to MAC A on PE3 will be interrupted.

Solution: The C-MAC Advertisement Route



C-MAC Advertisement Route Specific Content



- Originating MAC Route at the CE:
 - When a CE learns MAC addresses in the data plane in a given VLAN which is in the setting of VLANs across the Ethernet links attached to a given PE
- Receiving a MAC Route by the PE:
 - The PE SHOULD install forwarding state for the associated MAC addresses based on the Ethernet Segment and VLAN inferred from the MAC route.
 - the PE SHOULD advertises the MAC addresses it learns from CE in the control plane, to all the other PEs in the associated EVPN instance

Next Step

- Solicit comments and feedbacks
- Revise the draft