

Reseller Drafts Updates and Issues Under Discussion

Ning Kong

IETF94 EPPEXT @Yokohama

Background

- The thought of reseller extension was first mentioned at ROW@Dallas
- Receive interests (Verisign/SIDN/AFNIC)
- Continuous WG discussions on the mailing list
- 02-version submitted
 - draft-zhou-eppext-reseller-mapping-02
 - EPP mapping for provisioning and management of reseller object
 - draft-zhou-eppext-reseller-02
 - An reseller extension to EPP including reseller identifier and name (optional)

Relationship

- A reseller object defined in draft-zhou-eppext-reseller-mapping should be created first.
- The reseller information specified in draft-zhou-eppext-reseller should reference the existing reseller identifier and reseller name.
 - <reseller:id> ↔ <resellerext:id>
 - <reseller:name> ↔ <resellerext:name>

Update-URL Definition

- Explicitly refer the <reseller:url> to a URL
- Before
 - A <reseller:url> element that contains the reseller's web home page.
- After
 - A <reseller:url> element that contains the URL to the website of the reseller.

Update-Rename the Two Drafts

- draft-zhou-epnext-reseller-mapping
 - Change to draft-zhou-epnext-reseller
- draft-zhou-epnext-reseller
 - Change to draft-zhou-epnext-reseller-ext
- Update next version

Discussion-Status Value

- Status values defined in the draft refer to draft-arias-noguchi-dnrd-objects-mapping
 - ok: the normal status value for the reseller object.
 - readonly: transform commands submitted with the reseller identifier in the reseller extension would not be allowed.
 - terminated: query and transform commands submitted with the reseller identifier in the reseller extension would not be allowed.
- Mailinglist comment: reuse contact status values
 - clientDeleteProhibited, serverDeleteProhibited
 - clientUpdateProhibited, serverUpdateProhibited
 - linked
 - ok

Discussion-Postal Info Related Elements

- <reseller:postalInfo>: reuses postalInfo element to contain postal- address information. The required elements include,
 - <reseller:name>
 - <reseller:addr> (<reseller:city> and <reseller:cc>)
- Mailinglist comment: <reseller:tradingName> & <reseller:address> are used in SIDN and Nominet. The required elements include,
 - <reseller:tradingName> : identifying the organizational name of the reseller
 - <reseller:address>: the detailed address of a reseller

Next Step

- WG adoption ?
- RDAP Extension ?
 - Simple example
"reseller" : "Reseller Example",
 - Complex example

```
{  
  "objectClassName" : "reseller",  
  "handle" : "ANRESELLER",  
  "entities" :  
    {  
      "objectClassName" : "entity",  
      "handle" : "XXXX",  
      "vcardArray" : [  
        ...]  
    }  
}
```


Thank you!

Questions or comments?