

YANG Hardware Model

`draft-ietf-netmod-entity-01`

IETF 97

Martin Björklund
Andy Bierman
Jie Dong
Dan Romascanu

Changes since -00

Renamed top-level node to “hardware”.

Renamed list “physical-entity” to “component”.

Renamed the module “ietf-hardware”.

Avoid recursive definition by moving the base identity
“entity-physical-class” to iana-entity.yang.

Fixed bug in XPath syntax.

Issues – feedback from BBF 1(2)

Should the model support pre-configuration of hardware components?

Current config model

```
+--rw component* [name]
    +-rw name          string      // IDENTIFICATION
    +-rw serial-num?  string
    +-rw alias?        string
    +-rw asset-id?    string
    ...
    ...
```

Proposed config model

```
+--rw component* [name]
    +-rw name          string
    +-rw class         identityref // IDENTIFICATION
    +-rw contained-in leafref   // IDENTIFICATION
    +-rw parent-rel-pos int32    // IDENTIFICATION
    +-rw serial-num?  string
    +-rw alias?        string
    +-rw asset-id?    string
    ...
    ...
```

Issues – feedback from BBF 2(2)

Should we add a generic “reset” action?

```
list component {  
    ...  
    action reset {  
        description  
            "Request a reset of the component.";  
        input {  
            leaf reset-type {  
                type identityref {  
                    base reset-type;  
                }  
            }  
        }  
    }  
}
```