

Interface extensions YANG & VLAN sub-interface YANG Status update

draft-ietf-netmod-intf-ext-yang-04 &
draft-ietf-netmod-sub-intf-vlan-model-01

Rob Wilton (Cisco)

rwilton@cisco.com

IETF 98, NETMOD WG

draft-ietf-netmod-intf-ext-yang status:

- Feedback received from Lada and Acee
 - More feedback welcome - it would be good to get this module to WGLC
- Most comments have been addressed:
 - Open issues are covered on the next few slides.
- Also added a invalid destination MAC address drop counter to the Ethernet module.
- Would like to add Ethernet histogram counters (e.g. similar to the RMON MIB), which can't be standardized in 802.3 (will cover in Thursday's session)

Forwarding Mode Leaf - Open Issue 1

Defines whether the forwarding mode is:

optical, layer 2, or network layer

- Useful for some devices to optimize hardware programming
- Also would allow models to check configuration against forwarding layer constraints (e.g. don't apply an L2 ACL if the interface has been configured as L3 forwarding)

Issue:

- Questions have been raised on the naming, and definition of this leaf:
- Should we keep this leaf in the model?

Bandwidth Parameter - Open Issue 2

Issue:

- Should the interface bandwidth parameter be defined here?

Proposed resolution:

- Check with RTGWWG YANG Design Team, or otherwise remove this leaf.

Alternative resolution:

- Rename from “bandwidth” to “reservable-bandwidth”
- Align definition to maximum-reservable-bandwidth (RFC 3630, OSPF TE extensions)

Dataplane Loopback - Open Issue 3

Issue:

- Do we align dataplane loopback with the loopback configuration?
- Loopback is currently limited to physical interface loopback (internal, line, external)
- Could possibly align with L2 dataplane loopback (which is considerably more complex)
- Should the loopback configuration be ephemeral configuration rather than standard configuration?

draft-ietf-netmod-sub-intf-vlan-model-01 status:

Recently adopted as WG document

Minor updates only

Only one issue that I would like input on (now, later, or on email).

VLAN tag structure Issue

Issue: Is using an array the best choice here, rather than hard coded first tag, second tag, etc.

Current:

```
augment /if:interfaces/if:interface/if-cmn:encapsulation/
                                          if-cmn:encaps-type:
+--:(vlan)
  +--rw vlan
    +--rw tag* [index]
      +--rw index          uint8
      +--rw dot1q-tag
        +--rw tag-type     dot1q-tag-type
        +--rw vlan-id      ieee:vlanid
```

Issue 1 part 2

Alternative:

```
augment /if:interfaces/if:interface/if-cmn:encapsulation/
                                            if-cmn:encaps-type:
  +--:(vlan)
    +--rw vlan
      +--rw outer-tag
        | +--rw tag-type    dot1q-tag-type
        | +--rw vlan-id    ieee:vlanid
      +--rw second-tag
        +--rw tag-type    dot1q-tag-type
        +--rw vlan-id    ieee:vlanid
```


Next steps

Further reviews and comments please

Neither draft is particularly long, and it would be good to get them finished

Any questions?